

Vibro Till 8200



Field Cultivator

Vibro Till 8200 - Field Cultivator



Specifications

Sizes	• Single Fold - 26-1/2', 28-1/2', 30-1/2', & 32-1/2' • Double Fold - 36-1/2', 38-1/2', 40-1/2', 42-1/2', 44-1/2', 46-1/2', & 48-1/2'
Framework	• 4" (10.16 cm) x 4" (10.16 cm) x 1/4" (0.635 cm) wall thickness. Pull Frame members are 3/8" (0.953 cm) wall thickness. The framework is extruded through all frame members for added strength. • 6-Bar deep construction 162" (4.115 m)
Wheels	Single Fold: • Main Frame - 11L x 15 Tires, 12-ply, 8-bolt wheels • Wings - 9.5L x 15 Tires, 12-ply, 6-bolt wheels Double Fold: • Main Frame - 12.5L x 16.5 Tires, 14-ply, 8-bolt wheels • Inner Wings - 9.5L x 15 Tires, 12-ply, 6-bolt wheels • Outer Wings - 9.5L x 15 Tires, 12 ply, 6-bolt wheels
Choice of Tines	2 Piece Tine for 4" (10 cm) or 6" (15 cm) Spacing: • .524" thick (13.3 mm) Coil and Stem Assembly • .624" thick (16.3 mm) Coil and Stem Assembly
Hydraulics	Single Fold: • Main Frame Lift Cylinders - 3-3/4" x 8" (9.4 cm x 20 cm) • Wing Lift Cylinders - 3-1/2" x 8" (8.8 cm x 20 cm) • Fold Cylinders: • 26-1/2', 28-1/2', & 30-1/2' - 4" x 30" (10 cm x 76 cm) • 32-1/2' - 4-1/2" x 30" (11.43 cm x 76 cm)
Standard Features	• Self-Leveling Hitch • Single Point Hydraulics • Drop Leg Jack for use on front or rear of cultivator. • Safety Light Kit
Option	• Rear Hitch



Kongskilde Industries Inc.

Tel. +1 309-820-1090

mail@kus.kongskilde.com

www.kongskilde.com