

Kongskilde XRWT OL



Fully mounted reversible ploughs



Kongskilde XRWT OL is easy to turn over because of favorable geometry.

Fully mounted reversible on land /in furrow plough

Kongskilde ploughs are developed for farmers and contractors who focus on professional farming. Kongskilde ploughs have unique design and features that makes them reliable and economical over time.

Kongskilde XRWT OL

The new model of Kongskilde plough is based on the well proven XRWT. The main difference is the front end. XRWT OL has a new stronger headstock and turnover arm as it is available also as a seven furrow version.

The new Kongskilde XRWT OL is available from 5 up to 7 furrows and equipped with hydraulic adjustable furrow width.

- Rear mounted depth and transport wheel for best weight transfer and depth control. New stronger wheel arm mounted outside gives more space for residues.
- Designed for wide tractors, up to four meter fully on land.
- Easy to change between on land and in furrow ploughing.
- Separate alignment when ploughing in furrow. Saves time as the plough works like a standard plough and do not need to go out to on land position for reversing.



Combi wheel for roadwork.

Technical specification

Model	Number of furrows	Working width, cm	Weight, kg	Inter body clearance, cm	Under beam clearance, cm	Max. effect, kW	Approx. lift requirement, kg
XRWT OL 5975*	5	150 - 275	2.520	90	75/80	250	6.500
XRWT OL 6975*	6	180 - 330	2.820	90	75/80	350	8.500
XRWT OL 7975	7	210 - 385	3.120	90	75/80	350	11.000

X=Classification R=Reversible W= Hydraulically adjustable working width T= Tripped OL= Onland

*= Models can be extended with one extra furrow



Kongskilde XRWT OL in onland position.



Kongskilde XRWT OL in furrow position.

