Better fuel efficiency





Överum ploughs wins test



Överum XL-body has the lowest draft requirement among its competitors

A comparison of the three most common plough brands was also done by SLU. A 100 hp tractor was used to measure the draft requirement of the four furrow ploughs. The furrow width of ploughs was adjusted to 40 cm and the depth of the ploughing was 20 cm. As you can see on the diagram, the Överum plough with the XL-body was the one among the competitors which had the lowest draft requirement. This result means less slippage and higher efficiency which gives a lower fuel consumption and tillage cost.



kN/m² 180 Specific draft strength 166,0 160 137,8 140 125,2 120 100 96.1 84,0 83,5 80.7 80 60 40 20 0 Cult Plouah Plough Plough 17 cm 17 cm 21 cm 13 cm 21 cm

The fuel consumption and the use of the tractor are highly important for farmers to achieve a low cost cultivation. The Swedish University of Agriculture (SLU) has presented interesting findings on this subject.


Low draft requirement

With a 135 hp tractor, equipped with advanced measuring systems the energy consumption has been compared to the amount of moved soil of different soil preparation machines. The draft requirement and the amount of loose soil have been registered for the plough, the cultivator and disc tools at different depth adjustments. As you can see in the diagram, ploughing is the most efficient method for soil tillage.

Measuring of fuel consumption with a front mounted plough

There have been discussions around the economical benefits of driving with a fully mounted front plough instead of having a regular front weight on the tractor. SLU had come up with an answer after comparing these two options. They had a 135 hp

tractor and compared a four furrow plough together with a front weight and a four furrow plough together with a two furrow front mounted plough. On the test area (heavy clay soil) the fuelconsumption decreased from 18.4 litre/hectare to 16.5 litre/hectare. That is to say 10 % in decreased fuel consumption with a front mounted plough instead of a front weight. Practical measuring on lighter soil had



shown a decrease down to 8 litre/hec tare. The front mounted plough is also well adapted for use when shallow ploughing is required.

